

Shock Absorbing Lanyard - Technical Sales Sheet: 65

Product Code: 32115, 32116,
32117, 32118

Standards: EN355:2002,
Rfu II.062, Rfu II.063



Product Features

- Polyester webbing
- External tear Pack
- Velcro tear pack cover for easy inspection
- Double lock carabiner and scaff/rebar hook options
- RFID options available
- Reflective webbing
- Twin leg variant
- Contrasting stitching for easy inspection

Product Specification

- User Weight: 59kg - 140kg
- Working Length: 1.8m
- Product weight: 32115: 0.7kg
32116: 1.3kg
32117: 1.0kg
32118: 2.2kg
- Connector material: zinc plated steel
- Unstretched length: with scaff/rebar hook: 1.35m
with carabiner: 1.22m
- Webbing material: polyester



Shock Absorbing Lanyards

Model

SHFAL



ISO 9001:2015

Cert No.-24078-QMS-001

Description: Shock Absorbing Lanyards

Shock Absorbing Lanyard - Technical Sales Sheet: 65

Product Code: 32115, 32116,
32117, 32118

Standards: EN355:2002,
Rfu II.062, Rfu II.063



**Captive pin double lock
carabiner both ends.
Single leg.**



**Captive pin double
lock carabiner and
scaff/rebar hook.
Single leg.**



**Captive pin double
lock carabiner and
scaff/rebar hook.
Twin leg.**



**Captive pin double lock
carabiner both ends.
Twin leg**

Product Code	Description
32115	SHFAL-A01: 1.8m single leg with captive pin double lock carabiner both ends. User capacity: 140kg
32116	SHFAL-A02: 1.8m single leg with captive pin double lock carabiner and scaff/rebar hook. User capacity: 140kg
32117	SHFAL-A04: 1.8m twin leg with captive pin double lock carabiner both ends. User capacity: 140kg
32118	SHFAL-A03: 1.8m twin leg with captive pin double lock carabiner and scaff/rebar hook. User capacity: 140kg



Shock Absorbing Lanyards

Model

SHFAL



Cert No.-24078-QMS-001

ISO 9001:2015

Description: Shock Absorbing Lanyards